

ASRock MB AM4 A520M-HVS 90-MXBE60-A0UAYZ

Šifra: 81277

Kategorija proizvoda: MATIČNE PLOČE

Proizvođač: ASRock

Cena: 6.490,00 rsd



Memory

- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- AMD Ryzen series CPUs (Vermeer) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Matisse) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APUs (Cezanne) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APUs (Renoir) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- Max. capacity of system memory: 64GB**
- Supports Extreme Memory Profile (XMP) memory modules
- 15μ Gold Contact in DIMM Slots

CPU

- Support
- Series a
- 6 Powe

*Not cor
Ryzen™

Chipset

- AMD A520

BIOS

- 128Mb AMI UEFI Legal
- BIOS with GUI support
- Supports "Plug and Play"

- ACPI 5.1 compliance
- wake up events
- Supports jumperfree
- SMBIOS 2.3 support
- CPU, CPU VDDCR_SOC, DRAM, VDDP Voltage Multi-adjustment

Graphics

- Integrated AMD Radeon™ Vega Series Graphics in Ryzen Series APU*
- DirectX 12, Pixel Shader 5.0
- Shared memory default 2GB. Max Shared memory supports up to 16GB.**
- Dual graphics output: support D-Sub and HDMI ports by independent display controllers
- Supports HDMI 2.1 with max. resolution up to 4K x 2K (4096x2160) @ 60Hz
- Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz
- Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI 2.1 Port (Compliant HDMI monitor is required)
- Supports HDR (High Dynamic Range) with HDMI 2.1
- Supports HDCP 2.3 with HDMI 2.1 Port
- Supports 4K Ultra HD (UHD) playback with HDMI 2.1 Port
- Supports Microsoft® PlayReady

*Actual support may vary by CPU

**The Max shared memory 16GB requires 32GB system memory installed.

Audio

- 7.1 CH HD Audio (Realtek ALC887/897 Audio Codec)
- Supports Surge Protection

LAN

- PCIE x1 Gigabit LAN 10/100/1000 Mb/s
- Realtek RTL8111H
- Supports Wake-On-LAN
- Supports Lightning/ESD Protection
- Supports Energy Efficient Ethernet 802.3az
- Supports PXE

Slots

- 1 x PCI Express 3.0 x16 Slot (PCI-E2: x16 mode)*
- 1 x PCI Express 3.0 x1 Slot

*Supports NVMe SSD as boot disks

Storage

CPU:

- 1 x Ultra M.2 Socket (M2_1, Key M), supports type 2242/2260/2280 SATA3 6.0 Gb/s & PCIe Gen3x4 (32 Gb/s) modes*

Chipset:

- 4 x SATA3 6.0 Gb/s

Connectors

*Supports NVMe SSD as boot disks

Supports ASRock U.2 Kit

RAID

- Supports RAID 0, RAID 1 and RAID 10 for SATA storage devices

Connector

- 1 x SPI TPM Header
- 1 x COM Port Header
- 1 x Chassis Intrusion and Speaker Header
- 1 x CPU Fan Connector (4-pin)*

- 2 x Chassis Fan

Connectors (4-pin)

(Smart Fan Speed

Control)**

- 1 x 24 pin ATX Power

Connector

- 1 x 4 pin 12V Power

Connector

- 1 x Front Panel Audio

Connector

- 2 x USB 2.0 Headers

(Support 4 USB 2.0 ports)

(Supports ESD

Protection)

- 1 x USB 3.2 Gen1

Header (Supports 2 USB

3.2 Gen1 ports)

(Supports ESD

Protection)

*The CPU Fan Connector supports the CPU fan of maximum 1A (12W) fan power.

**The Chassis Fan supports the water cooler fan of maximum 1A (12W) fan power. CHA_FAN2 can auto detect if 3-pin or 4-pin fan is in use.

Rear Panel I/O

- 1 x PS/2

Mouse/Keyboard Port

- 1 x D-Sub Port

- 1 x HDMI Port
- 2 x USB 2.0 Ports
(Supports ESD Protection)
- 4 x USB 3.2 Gen1 Ports
(Supports ESD Protection)
- 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED)
- HD Audio Jacks: Line in / Front Speaker / Microphone

CPU

- Supports AMD AM4 Socket Ryzen™ 3000, 4000 G-Series and 5000 and 5000 G-Series Desktop Processors*
- 6 Power Phase design

*Not compatible with AMD Ryzen™ 5 3400G and Ryzen™ 3 3200G.

Memory

- Dual Channel DDR4 Memory Technology
- 2 x DDR4 DIMM Slots
- AMD Ryzen series CPUs (Vermeer) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series CPUs (Matisse) support DDR4 4600+(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APU's (Cezanne) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- AMD Ryzen series APU's (Renoir) support DDR4 4733+(OC) / 4666(OC) / 4600(OC) / 4533(OC) / 4466(OC) / 4400(OC) / 4333(OC) / 4266(OC) / 4200(OC) / 4133(OC) / 4000(OC) / 3866(OC) / 3800(OC) / 3733(OC) / 3600(OC) / 3466(OC) / 3200 / 2933 / 2667 / 2400 / 2133 ECC & non-ECC, un-buffered memory*
- Max. capacity of system memory: 64GB**
- Supports Extreme Memory Profile (XMP) memory modules
- 15µ Gold Contact in DIMM Slots

BIOS

- 128Mb AMI UEFI Legal BIOS with GUI support
- Supports "Plug and Play"
- ACPI 5.1 compliance
- Wakeup events
- AMI Secure Boot
- Supports jumperfree
- SMBIOS 2.3 support
- CPU, CPU VDDCR_SOC, DRAM, VDDP Voltage Multi-adjustment

Graphics

- Integrated AMD Radeon™ Vega Series Graphics in Ryzen Series APU*
- DirectX 12, Pixel Shader 5.0
- Shared memory default 2GB. Max Shared memory supports up to 16GB.**
- Dual graphics output: support D-Sub and HDMI ports by independent display controllers
- Supports HDMI 2.1 with max. resolution up to 4K x 2K (4096x2160) @ 60Hz
- Supports D-Sub with max. resolution up to 1920x1200 @ 60Hz
- Supports Auto Lip Sync, Deep Color (12bpc), xvYCC and HBR (High Bit Rate Audio) with HDMI 2.1 Port (Compliant HDMI monitor is required)
- Supports HDR (High Dynamic Range) with HDMI 2.1
- Supports HDCP 2.3 with HDMI 2.1 Port
- Supports 4K Ultra HD (UHD) playback with HDMI 2.1 Port
- Supports Microsoft®

PlayReady

*Actual support may vary
by CPU

**The Max shared
memory 16GB requires
32GB system memory
installed.

Audio

- 7.1 CH HD Audio
(Realtek ALC887/897
Audio Codec)
- Supports Surge
Protection

LAN

- PCIE x1 Gigabit LAN
10/100/1000 Mb/s
- Realtek RTL8111H
- Supports Wake-On-LAN
- Supports Lightning/ESD
Protection
- Supports Energy
Efficient Ethernet

802.3az

- Supports PXE

Slots

- 1 x PCI Express 3.0 x16
Slot (PCIe2: x16 mode)*
- 1 x PCI Express 3.0 x1
Slot

*Supports NVMe SSD as
boot disks

Storage

CPU:

- 1 x Ultra M.2 Socket
(M2_1, Key M), supports
type 2242/2260/2280
SATA3 6.0 Gb/s & PCIe
Gen3x4 (32 Gb/s)
modes*

Chipset:

- 4 x SATA3 6.0 Gb/s

Connectors

*Supports NVMe SSD as
boot disks

Supports ASRock U.2 Kit

RAID

- Supports RAID 0, RAID
1 and RAID 10 for SATA
storage devices

Connector

- 1 x SPI TPM Header
- 1 x COM Port Header
- 1 x Chassis Intrusion
and Speaker Header
- 1 x CPU Fan Connector
(4-pin)*
- 2 x Chassis Fan
Connectors (4-pin)
(Smart Fan Speed
Control)**

- 1 x 24 pin ATX Power
Connector

- 1 x 4 pin 12V Power
Connector

- 1 x Front Panel Audio
Connector

- 2 x USB 2.0 Headers
(Support 4 USB 2.0 ports)
(Supports ESD
Protection)
- 1 x USB 3.2 Gen1
Header (Supports 2 USB
3.2 Gen1 ports)
(Supports ESD
Protection)

*The CPU Fan Connector
supports the CPU fan of
maximum 1A (12W) fan
power.

**The Chassis Fan
supports the water cooler
fan of maximum 1A
(12W) fan power.
CHA_FAN2 can auto
detect if 3-pin or 4-pin
fan is in use.

Rear Panel I/O

- 1 x PS/2
Mouse/Keyboard Port
- 1 x D-Sub Port
- 1 x HDMI Port
- 2 x USB 2.0 Ports
(Supports ESD
Protection)
- 4 x USB 3.2 Gen1 Ports
(Supports ESD
Protection)
- 1 x RJ-45 LAN Port with
LED (ACT/LINK LED and
SPEED LED)
- HD Audio Jacks: Line in /
Front Speaker /
Microphone