

Gembird EG-UPS-001 UPS sa stabilizatorom 650VA 4xschuko

Šifra: 81642

Kategorija proizvoda: UPS I PRENAPONSKE ZAŠTITE

Proizvođač: GEMBIRD

Cena: 7.990,00 rsd



UPS
with
AVR,
650
VA

ULTIMATE DEFENCE

Table top design

Provides backup power - prevents data loss

Protects your sensitive and valuable equipment

Compact and reliable - ideal for home and small office use

Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7Ah

Charge time: up to 12 hours

Sockets: 1 x C13 (input), 4 x Schuko (output)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 650 VA (390 W)

Charging current: up to 1.2 A

Noise: 45 dB at 1 m distance

Dimensions: 280 x 185 x 95 mm

Product weight: 4.5 kg

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS.

For example, a 700 W UPS needs at least a connected load of 35 W to work.

ups mustek apc

UPS with AVR, 650 VA

ULTIMATE DEFENCE

Table top design

Provides backup power - prevents data loss

Protects your sensitive and valuable equipment

Compact and reliable - ideal for home and small office use

Specifications

Type: line interactive

Waveform: sine wave (AC mains), modified (square) sine wave (battery)

Input: 220 V AC $\pm 25\%$, 50 / 60 Hz $\pm 10\%$

Output: 220 V AC $\pm 10\%$, 50 / 60 Hz $\pm 1\%$ (220 V AC $\pm 5\%$ at inverter mode)

Switching time: less than 10 ms

Backup time: 10...30 mins (depends on the load)

Battery: sealed lead-acid 12 V DC / 7Ah

Charge time: up to 12 hours

Sockets: 1 x C13 (input), 4 x Schuko (output)

Operating conditions: 0°C~40°C, at humidity 20~90%RH non condensing

Power: 650 VA (390 W)

Charging current: up to 1.2 A

Noise: 45 dB at 1 m distance

Dimensions: 280 x 185 x 95 mm

Product weight: 4.5 kg

System requirements

In order to work correctly, the connected load should be at least 5% of the maximum capacity of the UPS.

For example, a 700 W UPS needs at least a connected load of 35 W to work.

ups mustek apc