

## Cudy POE25 30W Gigabit PoE+/PoE Injector, 2-Channel Outdoor PoE Extender, 100m

Šifra: 89569

Kategorija proizvoda: MREŽNA OPREMA

Proizvođač: CUDY

**Cena: 8.020,00 rsd**



2-

Channel Outdoor Gigabit PoE Extender, Model:

POE25  
Kompatibilan sa IEEE802.3af i IEEE802.3at,  
Proširuje domet PoE i Ethernet-a za dodatnih 100 metara,  
Nije potrebno dodatno napajanje,  
Automatski otkriva i štiti PoE opremu od postojanja oštećeni pogrešnom instalacijom,  
Mreža pune brzine na celoj produženoj udaljenosti,  
Kompaktna veličina, dizajn za montažu na zid,  
Jednostavna plug-and-play instalacija,  
EMI standardi su u skladu sa FCC, CE klasom B

Product Name: POE25

No. of channels: 1(PoE IN) into 2(PoE OUT)

Pass Through Data Rates: 10/100/1000 Mbps half/full duplex

Power over Ethernet input: Pin Assignment and Polarity: Both 1/2(-),3/6(+) and 4/5(+),7/8(-)

Power over Ethernet Output: Pin Assignment and Polarity :1/2(+),3/6(-), Output Power: up to 30W for 2 PSE

Connectors: Shielded RJ-45, EIA 568A and 568B

Network cables: Shielded category 5 (or higher)

Dimensions: 230mm x 90mm x 40mm

Mounting: Wall or shelf

Environment: Indoor or Outdoor

Environmental Conditions:

- Operating Ambient Temperature: Operating Ambient Temperature: -25: to 55 °C

- Operating Humidity: Complies with IP67(Support Outdoor rain prevention, need outdoor waterproof UTP cable)

- Storage Temperature:-40 to 70 °C

Regulatory Compliance: IEEE 802.3af (15.4W), IEEE 802.3at (30W), IEEE802.3at 4Pairs(60W)

2-Channel Outdoor Gigabit PoE Extender, Model: POE25

Kompatibilan sa IEEE802.3af i IEEE802.3at,

Proširuje domet PoE i Ethernet-a za dodatnih 100 metara,

Nije potrebno dodatno napajanje,

Automatski otkriva i štiti PoE opremu od postojanja oštećeni pogrešnom instalacijom,

Mreža pune brzine na celoj produženoj udaljenosti,

Kompaktna veličina, dizajn za montažu na zid,

Jednostavna plug-and-play instalacija,

EMI standardi su u skladu sa FCC, CE klasom B

Product Name: POE25

No. of channels: 1(PoE IN) into 2(PoE OUT)

Pass Through Data Rates: 10/100/1000 Mbps half/full duplex

Power over Ethernet input: Pin Assignment and Polarity: Both 1/2(-),3/6(+) and 4/5(+),7/8(-)

Power over Ethernet Output: Pin Assignment and Polarity :1/2(+),3/6(-), Output Power: up to 30W for 2 PSE

Connectors: Shielded RJ-45, EIA 568A and 568B

Network cables: Shielded category 5 (or higher)

Dimensions: 230mm x 90mm x 40mm

Mounting: Wall of shelf

Environment: Indoor or Outdoor

Environmental Conditions:

- Operating Ambient Temperature: Operating Ambient Temperature: -25: to 55 ?

- Operating Humidity: Complies with IP67(Support Outdoor rain prevention,need outdoor waterproof UTP cable)

- Storage Temperature:-40 to 70 C

Regulatory Compliance: IEEE 802.3af (15.4W), IEEE 802.3at (30W), IEEE802.3at 4Pairs(60W)