

60W

Cudy POE300 60W Gigabit PoE+/PoE Injector, 802.3at/802.3af Standard, Data&Power 100 Meters

Šifra: 89680
Kategorija proizvoda: MREŽNA OPREMA
Proizvođač: CUDY

Cena: 2.640,00 rsd



Gigabit PoE+/PoE Injector

- Up to 60 watts PoE power supply
- 1 10/100/1000M Ethernet Input port
- 1 10/100/1000M PoE Output port
- IEEE 802.3at / IEEE 802.3af standard compliant
- Plug&play, simple setup with no configuration needed

Model POE300

No. of channels 1

Pass Through Data Rates 10/100/1000Mbps

Power over Ethernet Output

Pin Assignment and Polarity: 1/2 (-), 3/6 (+), 4/5 (+), 7/8 (-),

Output Power Voltage: 50Vdc

User Port Power: 60W

Input Power Requirements AC Input Voltage: 100 to 240 VAC

AC Input Current: 0.5A 100-240 VAC

AC Frequency: 50 to 60 Hz

Dimensions 145mm x 60mm x 40mm

Indicators System Indicator: AC Power

User Indicator: Channel Power

Connectors Shielded RJ-45, EIA 568A and 568B

Regulatory Compliance IEEE 802.3af (15.4W)

IEEE 802.3at (30W)

IEEE802.3at 4Pairs(60W)

Environmental Conditions Operating Ambient Temperature:0 to 45c

Operating Humidity:Maximum 80%, Non-condensing

Storage Temperature:-20 to 70c

Storage Humidity:Maximum 80%, Non-condensing

60W Gigabit PoE+/PoE Injector

- Up to 60 watts PoE power supply
- 1 10/100/1000M Ethernet Input port
- 1 10/100/1000M PoE Output port
- IEEE 802.3at / IEEE 802.3af standard compliant
- Plug&play, simple setup with no configuration needed

Model POE300

No. of channels 1

Pass Through Data Rates 10/100/1000Mbps

Power over Ethernet Output

Pin Assignment and Polarity: 1/2 (-), 3/6 (+),4/5 (+), 7/8 (-),

Output Power Voltage: 50Vdc

User Port Power: 60W

Input Power Requirements AC Input Voltage: 100 to 240 VAC

AC Input Current: 0.5A 100-240 VAC

AC Frequency: 50 to 60 Hz

Dimensions 145mm x 60mm x 40mm

Indicators System Indicator: AC Power

User Indicator: Channel Power

Connectors Shielded RJ-45, EIA 568A and 568B

Regulatory Compliance IEEE 802.3af (15.4W)

IEEE 802.3at (30W)

IEEE802.3at 4Pairs(60W)

Environmental Conditions Operating Ambient Temperature:0 to 45c

Operating Humidity:Maximum 80%, Non-condensing

Storage Temperature:-20 to 70c

Storage Humidity:Maximum 80%, Non-condensing