

Cudy LT400 Outdoor 4G LTE Cat 4 N300 Wi-Fi Router, Nano SIM Slot, 10/100Mbps WAN/LAN

Šifra: 89699

Kategorija proizvoda: MREŽNA OPREMA

Proizvođač: CUDY

Cena: 6.100,00 rsd

- N300 Wi-Fi
- 1x 10/100Mbps WAN/LAN
- Nano SIM Slot
- 24V Passive PoE
- 2x Internal WiFi Antennas + 2x Detachable 4G Antennas
- VPN & DDNS
- IP65 WaterProof

Turn Everywhere 4G into N300 Wi-Fi

With 4G Cat.4 standards, LT400 Outdoor communicates with a 4G tower with speeds of up to 150 Mbps download and 50 Mbps upload. It features a N300 Wi-Fi, providing reliable network for web browsing, video streaming, surveillance, and POS services.

Boosted Wi-Fi Coverage with Beamforming

Tested Wi-Fi coverage performance in four different scenarios, achieved by Beamforming technology and two built-in antennas. If your space is too large for one Cudy 4G Outdoor Router to cover, you can expand your Wi-Fi coverage into a Mesh network by adding another Cudy AP.

LTE Module Model EU Version:

-EC200A-EU

-LTE-FDD: B1/B3/B7/B8/B20/B28A

-LTE-TDD: B38/B40/B41

-WCDMA: B1/B8

-GSM/EDGE: B3/B8

LTE Module Model US Version:

-EC25-AFXD

-LTE-FDD: B2/B4/B5/B12/B13/B14/B66/B71

-WCDMA: B2/B4/B5

Flash: 64 Mbit (8 MB) Flash

DDR: 512 Mbit (64 MB) DDR

Interface:

1x 10/100Mbps WAN/LAN RJ45 Port (24V/0.5A passive PoE, 4/5+, 7/8-)

1x Reset Button

1x Nano SIM Slot



FDD/TDD Cat 4 with detachable antenna

- LTE

LED: System/Internet/Ethernet/2.4G WiFi/5GHz WiFi/Signal Strength

Antenna:

2× Internal Wi-Fi Antennas

2× External Detachable 4G Antennas

Gain: 5 dBi

Wireless Standards: IEEE 802.11n

Frequency: 2.4 GHz

Signal Rate: 300 Mbps (2.4 GHz) / Compatible with 802.11b/g/n Wi-Fi standards

Transmit Power CE: 20dBm

FCC:30dBm

Wireless Modes: Enable/Disable Wireless Radio, WMM

Wireless Security: WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK

Mesh Compatibility: Works with other Cudy Mesh products (as the main Mesh node)

WAN Type: 4G/Dynamic IP/Static IP/PPPoE

DHCP: Server, DHCP Client List, Address Reservation

Dynamic DNS: Compatible with 15 more DDNS providers

NAT: Port Forwarding, Port Triggering, UPnP, DMZ

VPN Sever & Client: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier

CWMP Protocol: TR069 / TR098 / TR111 / TR181

ACS Server Compatibility: GenieACS, OpenACS

Management: Access Control, Local Management, Remote Management, Wake on LAN

TTL: Extend/Spoof/Custom

DNS: Cloudflare/Google/Quad9/Custom

Internet Protocols: IPv4 / IPv6

IPv6:

-Relay

-Dynamic(SLAAC/DHCPv6)

-Static (Fixed IP)

-Passthrough

-MAP-E (Dual-stack)

-DS-Lite (Dual-stack)

- LTE FDD/TDD Cat 4 with detachable antenna

- N300 Wi-Fi

- 1× 10/100Mbps WAN/LAN

- Nano SIM Slot

- 24V Passive PoE

- 2× Internal WiFi Antennas + 2× Detachable 4G Antennas

- VPN & DDNS

- IP65 WaterProof

Turn Everywhere 4G into N300 Wi-Fi

With 4G Cat.4 standards, LT400 Outdoor communicates with a 4G tower with speeds of up to 150 Mbps download and 50 Mbps upload. It features a N300 Wi-Fi, providing reliable network for web browsing, video streaming, surveillance, and POS services.

Boosted Wi-Fi Coverage with Beamforming

Tested Wi-Fi coverage performance in four different scenarios, achieved by Beamforming technology and two built-in antennas. If your space is too large for one Cudy 4G Outdoor Router to cover, you can expand your Wi-Fi coverage into a Mesh network by adding another Cudy AP.

LTE Module Model EU Version:

-EC200A-EU

-LTE-FDD: B1/B3/B7/B8/B20/B28A

-LTE-TDD: B38/B40/B41

-WCDMA: B1/B8

-GSM/EDGE: B3/B8

LTE Module Model US Version:

-EC25-AFXD

-LTE-FDD: B2/B4/B5/B12/B13/B14/B66/B71

-WCDMA: B2/B4/B5

Flash: 64 Mbit (8 MB) Flash

DDR: 512 Mbit (64 MB) DDR

Interface:

1× 10/100Mbps WAN/LAN RJ45 Port (24V/0.5A passive PoE, 4/5+,7/8-)

1× Reset Button

1× Nano SIM Slot

LED: System/Internet/Ethernet/2.4G WiFi/5GHz WiFi/Signal Strength

Antenna:

2× Internal Wi-Fi Antennas

2× External Detachable 4G Antennas

Gain: 5 dBi

Wireless Standards: IEEE 802.11n

Frequency: 2.4 GHz

Signal Rate: 300 Mbps (2.4 GHz) / Compatible with 802.11b/g/n Wi-Fi standards

Transmit Power CE: FCC:Wireless Modes: Enable/Disable Wireless Radio, WMM

Wireless Security: WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK

Mesh Compatibility: Works with other Cudy Mesh products (as the main Mesh node)

WAN Type: 4G/Dynamic IP/Static IP/PPPoE

DHCP: Server, DHCP Client List, Address Reservation

Dynamic DNS: Compatible with 15 more DDNS providers

NAT: Port Forwarding, Port Triggering, UPnP, DMZ

VPN Sever & Client: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier

CWMP Protocol: TR069 / TR098 / TR111 / TR181

ACS Server Compatibility: GenieACS, OpenACS

Management: Access Control, Local Management, Remote Management, Wake on LAN

TTL: Extend/Spoof/Custom

DNS: Cloudflare/Google/Quad9/Custom

Internet Protocols: IPv4 / IPv6

IPv6:

-Relay

-Dynamic(SLAAC/DHCPv6)

-Static (Fixed IP)

-Passthrough

-MAP-E (Dual-stack)

-DS-Lite (Dual-stack)