Firma: Tempo Tehnika
Adresa: Dr Zorana Đinđića 13
Telefon: 034 33 33 35
PEPDV: REGPDV-746482
PIB: 101038590
E-mail: internetprodaja@tempo-tehnika.rs

- LTE

Cudy LT400 Outdoor 4G LTE Cat 4 N300 Wi-Fi Router, Nano SIM Slot, 10/100Mbps WAN/LAN

Šifra: 89699
Kategorija prozivoda: MREŽNA OPREMA
Proizvođač: CUDY

Cena: 6.100,00 rsd

FDD/TDD Cat 4 with detachable antenna

- N300 Wi-Fi
- 1× 10/100Mbps WAN/LAN
- Nano SIM Slot
- 24V Passive PoE
- 2× Internal WiFi Antennas + 2× Detachable 4G Antennas
- VPN & DDNS
- IP65 WaterProof

Turn Everywhere 4G into N300 Wi-Fi
With 4G Cat.4 standards, LT400 Outdoor communicates with a 4G tower with speeds of up to 150 Mbps download and 50 Mbps upload. It features a N300 Wi-Fi, providing reliable network for web browsing,video streaming, surveilance, and POS services.

Boosted Wi-Fi Coverage with Beamforming
Tested Wi-Fi coverage performance in four di?erent scenarios, achieved by Beamforming technology and two built-in antennas. If your space is too large for one Cudy 4G Outdoor Router to cover, you can expand your Wi-Fi coverage into a Mesh network by adding another Cudy AP.

LTE Module Model EU Version:
-EC200A-EU
-LTE-FDD: B1/B3/B7/B8/B20/B28A
-LTE-TDD: B38/B40/B41
-WCDMA: B1/B8
-GSM/EDGE: B3/B8

LTE Module Model US Version:
-EC25-AFXD
-LTE-FDD: B2/B4/B5/B12/B13/B14/B66/B71
-WCDMA: B2/B4/B5

Flash: 64 Mbit (8 MB) Flash
DDR: 512 Mbit (64 MB) DDR

Interface:
1× 10/100Mbps WAN/LAN RJ45 Port (24V/0.5A passive PoE, 4/5+,7/8-)
1× Reset Button
1× Nano SIM Slot

LED: System/Internet/Ethernet/2.4G WiFi/5GHz WiFi/Signal Strength
Antenna:
2× Internal Wi-Fi Antennas
2× External Detachable 4G Antennas
Gain: 5 dBi

Wireless Standards: IEEE 802.11n
Frequency: 2.4 GHz
Signal Rate: 300 Mbps (2.4 GHz) / Compatible with 802.11b/g/n Wi-Fi standards
Transmit Power CE: 20dBm
FCC:30dBm
Wireless Modes: Enable/Disable Wireless Radio, WMM
Wireless Security: WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK
Mesh Compatibility: Works with other Cudy Mesh products (as the main Mesh node)

WAN Type: 4G/Dynamic IP/Static IP/PPPoE
DHCP: Server, DHCP Client List, Address Reservation
Dynamic DNS: Compatible with 15 more DDNS providers
NAT: Port Forwarding, Port Triggering, UPnP, DMZ
VPN Sever & Client: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier
CWMP Protocol: TR069 / TR098 / TR111 / TR181
ACS Server Compatibility: GenieACS, OpenACS
Management: Access Control, Local Management, Remote Management, Wake on LAN
TTL: Extend/Spoof/Custom
DNS: Cloud?are/Google/Quad9/Custom
Internet Protocols: IPv4 / IPv6
IPv6:
-Relay
-Dynamic(SLAAC/DHCPv6)
-Static (Fixed IP)
-Passthrough
-MAP-E (Dual-stack)
-DS-Lite (Dual-stack)
- LTE FDD/TDD Cat 4 with detachable antenna
- N300 Wi-Fi
- 1× 10/100Mbps WAN/LAN
- Nano SIM Slot
- 24V Passive PoE
- 2× Internal WiFi Antennas + 2× Detachable 4G Antennas
- VPN & DDNS
- IP65 WaterProof

Turn Everywhere 4G into N300 Wi-Fi
With 4G Cat.4 standards, LT400 Outdoor communicates with a 4G tower with speeds of up to 150 Mbps download and 50 Mbps upload. It features a N300 Wi-Fi, providing reliable network for web browsing,video streaming, surveilance, and POS services.

Boosted Wi-Fi Coverage with Beamforming
Tested Wi-Fi coverage performance in four di?erent scenarios, achieved by Beamforming technology and two built-in antennas. If your space is too large for one Cudy 4G Outdoor Router to cover, you can expand your Wi-Fi coverage into a Mesh network by adding another Cudy AP.

LTE Module Model EU Version:
-EC200A-EU
-LTE-FDD: B1/B3/B7/B8/B20/B28A
-LTE-TDD: B38/B40/B41
-WCDMA: B1/B8
-GSM/EDGE: B3/B8

LTE Module Model US Version:
-EC25-AFXD

-LTE-FDD: B2/B4/B5/B12/B13/B14/B66/B71
-WCDMA: B2/B4/B5

Flash: 64 Mbit (8 MB) Flash
DDR: 512 Mbit (64 MB) DDR

Interface:
1× 10/100Mbps WAN/LAN RJ45 Port (24V/0.5A passive PoE, 4/5+,7/8-)
1× Reset Button
1× Nano SIM Slot

LED: System/Internet/Ethernet/2.4G WiFi/5GHz WiFi/Signal Strength
Antenna:
2× Internal Wi-Fi Antennas
2× External Detachable 4G Antennas
Gain: 5 dBi

Wireless Standards: IEEE 802.11n
Frequency: 2.4 GHz
Signal Rate: 300 Mbps (2.4 GHz) / Compatible with 802.11b/g/n Wi-Fi standards
Transmit Power CE: 20dBm
FCC:30dBm
Wireless Modes: Enable/Disable Wireless Radio, WMM
Wireless Security: WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK
Mesh Compatibility: Works with other Cudy Mesh products (as the main Mesh node)

WAN Type: 4G/Dynamic IP/Static IP/PPPoE
DHCP: Server, DHCP Client List, Address Reservation
Dynamic DNS: Compatible with 15 more DDNS providers
NAT: Port Forwarding, Port Triggering, UPnP, DMZ
VPN Sever & Client: PPTP/L2TP/OpenVPN/WireGuard/IPSec/Zerotier
CWMP Protocol: TR069 / TR098 / TR111 / TR181
ACS Server Compatibility: GenieACS, OpenACS
Management: Access Control, Local Management, Remote Management, Wake on LAN
TTL: Extend/Spoof/Custom
DNS: Cloud?are/Google/Quad9/Custom
Internet Protocols: IPv4 / IPv6
IPv6:
-Relay
-Dynamic(SLAAC/DHCPv6)
-Static (Fixed IP)
-Passthrough
-MAP-E (Dual-stack)
-DS-Lite (Dual-stack)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.