

## Cudy R700 Gigabit Multi-WAN VPN Router, 1Gbit WAN, 3Gibit LAN/WAN, 1Gbit LAN, 128MB DDR, 16MB NOR FI

Šifra: 89703

Kategorija proizvoda: MREŽNA OPREMA

Proizvođač: CUDY

**Cena: 4.330,00 rsd**

Gigabit WAN port

- 3 gigabitna WAN/LAN porta
- 1 Gigabit LAN port
- Multi-VAN balansiranje opterećenja
- PPTP/L2TP/OpenVPN/VireGuard/IPsec VPN server
- PPTP/L2TP/OpenVPN/VireGuard/IPsec VPN klijent
- Zerotier za daljinski pristup i izgradnju udaljene pod mreže
- DNS preko Cloudflare/NektDNS/Google
- Obilni sigurnosni mehanizmi
- Kompaktno i izdržljivo metalno kućište

### Standardi i protokoli:

IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE 802.3k, IEEE 802.1k

TCP/IP, DHCP, ICMP, NAT, PPPoE, HTTP, DNS,

IPSec, PPTP, L2TP, OpenVPN, VireGuard, Zerotier

### Interfejs:

- 1 Gigabit WAN port
- 3 Gigabit LAN/WAN porta
- 1 Gigabitni LAN portovi

### Mrežni mediji:

- 10BASE-T: UTP kategorija 3, 4, 5 kabl (maks. 100 m)
- EIA/TIA-568 1000 STP (maks. 100 m)
- 100BASE-TKS: UTP kategorija 5, 5e kabl (maks. 100 m)
- EIA/TIA-568 1000 STP (maks. 100 m)
- 1000BASE-T: UTP kategorija 5e, 6 kabl (maks. 100 m)

Dugme: Reset dugme

Napajanje: eksterni 12V/1A DC adapter

Flash: 16 MB NOR Flash

DRAM: 128 MB DDR

LED: PWR, SIS, WAN (Link/Act), LAN (Link/Act)

Dimenzije: 119×85×28 mm

- 1 Gigabit WAN port
- 3 gigabitna WAN/LAN porta
- 1 Gigabit LAN port
- Multi-VAN balansiranje opterećenja

- PPTP/L2TP/OpenVPN/VireGuard/IPsec VPN server
- PPTP/L2TP/OpenVPN/VireGuard/IPsec VPN klijent
- Zerotier za daljinski pristup i izgradnju udaljene pod mreže
- DNS preko Cloudflare/NektDNS/Google
- Obilni sigurnosni mehanizmi
- Kompaktno i izdržljivo metalno kućište

#### Standardi i protokoli:

IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE 802.3k, IEEE 802.1k  
 TCP/IP, DHCP, ICMP, NAT, PPPoE, HTTP, DNS,  
 IPSec, PPTP, L2TP, OpenVPN, VireGuard, Zerotier

#### Interfejs:

- 1 Gigabit WAN port
- 3 Gigabit LAN/WAN porta
- 1 Gigabitni LAN portovi

#### Mrežni mediji:

- 10BASE-T: UTP kategorija 3, 4, 5 kabl (maks. 100 m)
- EIA/TIA-568 1000 STP (maks. 100 m)
- 100BASE-TKS: UTP kategorija 5, 5e kabl (maks. 100 m)
- EIA/TIA-568 1000 STP (maks. 100 m)
- 1000BASE-T: UTP kategorija 5e, 6 kabl (maks. 100 m)

Dugme: Reset dugme

Napajanje: eksterni 12V/1A DC adapter

Flash: 16 MB NOR Flash

DRAM: 128 MB DDR

LED: PWR, SIS, WAN (Link/Act), LAN (Link/Act)

Dimenzije: 119×85×28 mm