Mercusys LAN Router MW306R N300

Šifra: 91019
Kategorija prozivoda: MREŽNA OPREMA
Proizvođač: MERCUSYS

Cena: 1.320,00 rsd

Wireless
Wireless Standards

IEEE 802.11 b/g/n
Frequency
2.4-2.5 GHz
WiFi Speeds
• 11n: Up to 300Mbps (Dynamic)
• 11g: Up to 54Mbps (Dynamic)
• 11b: Up to 11Mbps (Dynamic)
Reception Sensitivity
• 270M: -70dBm@10% PER • 11M: -87dBm@10% PER
• 130M: -72dBm@10% PER • 6 M: -92dBm@10% PER
• 54M: -74dBm@10% PER • 1 M: -94dBm@10% PER
Transmission Power
<20dBm (EIRP)
Wireless Security
WPA-PSK/WPA2-PSK
Wireless Functions
Enable/Disable Wireless Radio, WDS Bridging
Software
WAN Type
Dynamic IP/Static IP/PPPoE/PPTP/L2TP
Management
Access Control
Local Management
Remote Management
DHCP
DHCP Server, DHCP Client List
Port Forwarding
Virtual Server, UPnP, DMZ
Firewall Security
IP and MAC Address Binding
Guest Network
2.4GHz Guest Network
Hardware
Dimensions
5.8 × 4.5 × 1.3 in (147 × 115 × 34 mm)
Button
RESET/WPS Button
External Power Supply

5V/0.6A
Antenna Type
3* Fixed Antennas
Ethernet Ports
1* 10/100Mbps WAN Port,
3* 10/100Mbps LAN Ports
Others
Package Contents
Wi-Fi N Router (MW306R)
Power Adapter
Quick Installation Guide
Ethernet Cable
Environment
• Operating Temperature: 0°C~40°C (32°F~104°F)
• Operating Humidity: 10%~90% Non-Condensing

Wireless
Wireless Standards
IEEE 802.11 b/g/n
Frequency
2.4-2.5 GHz
WiFi Speeds
• 11n: Up to 300Mbps (Dynamic)
• 11g: Up to 54Mbps (Dynamic)
• 11b: Up to 11Mbps (Dynamic)
Reception Sensitivity
• 270M: -70dBm@10% PER • 11M: -87dBm@10% PER
• 130M: -72dBm@10% PER • 6 M: -92dBm@10% PER
• 54M: -74dBm@10% PER • 1 M: -94dBm@10% PER
Transmission Power
<20dBm (EIRP)
Wireless Security
WPA-PSK/WPA2-PSK
Wireless Functions
Enable/Disable Wireless Radio, WDS Bridging
Software
WAN Type
Dynamic IP/Static IP/PPPoE/PPTP/L2TP
Management
Access Control
Local Management
Remote Management
DHCP
DHCP Server, DHCP Client List
Port Forwarding
Virtual Server, UPnP, DMZ
Firewall Security
IP and MAC Address Binding
Guest Network
2.4GHz Guest Network
Hardware
Dimensions
5.8 × 4.5 × 1.3 in (147 × 115 × 34 mm)
Button
RESET/WPS Button
External Power Supply
5V/0.6A
Antenna Type
3* Fixed Antennas
Ethernet Ports

1* 10/100Mbps WAN Port,
3* 10/100Mbps LAN Ports
Others
Package Contents
Wi-Fi N Router (MW306R)
Power Adapter
Quick Installation Guide
Ethernet Cable
Environment
• Operating Temperature: 0°C~40°C (32°F~104°F)
• Operating Humidity: 10%~90% Non-Condensing